



GYPSEMNA

REGULAR

GYPSUM BOARD
RG - 16mm



■ DESCRIPTION

The Gypsemna's REGULAR (RG - 16mm) Type C Gypsum Board is an interior gypsum board consisting of a solid set , Type C gypsum core enclosed in GRAY - colored face paper and a strong liner back paper . Gypsemna's RG Type C board . Long edges are slightly tapered , allowing joints to be reinforced and concealed with joint tape and joint compound . The face paper and the back paper are 100 % recycled.

■ BASIC USES

The Gypsemna's REGULAR (RG-16 mm) Type C Gypsum Board is used for interior walls and ceilings in all building categories applications. It can be used for new construction or renovations steel framing . The boards are typically screwed to studs spaced maximum (600 mm) also can be applied by lamination or with the use of an adhesive.

■ ADVANTAGES

- Consistently high quality.
- Uniformly flat , attractive appearance , no shadows.
- Uniform high - strength cores eliminate crumbling , cracking.
- Edge tapers consistent to form perfect joints.
- Excellent thermal barrier and sound attenuation qualities.
- Green certified & Qualifies as a low VOC.

■ TECHNICAL DATA

PHYSICAL PROPERTIES

Thickness, Nominal
Width, Nominal
Length, Standard
Weight, Nominal
Edges
Color

16 mm
1200 mm
2400 , 3000 mm
10.75 kg/m²
TE , SE
Gray Color

FIRE RESISTANCE - ASTM E84

Core Type
Combustibility
Surface Burning Characteristics
Flame Spread
Smoke Development

Type C
Non - combustible core
Class A1
0
15

■ STANDARDS & REFERENCES

ASTM C1396

Product standard compliance

ASTM C473

Standard test methods for physical testing of gypsum panel products.

ASTM C840

Standard specification for application and finishing of gypsum board.

ASTM E84

Standard test method for surface burning Characteristics of building material

EN 520

Type A , performance of gypsum plasterboards.