




GYPSEMNA U TRACK

METAL PROFILES




DESCRIPTION

Gypsemna's U TRACK section provides a friction for the stud, which not only holds the studs in position until the lining board is fitted, but also helps in aligning the boards. Components for drywall stud and track products are cold roll-formed from hot-dipped galvanized steel (corrosion resistant) and are available in a variety of sizes and thicknesses.

BASIC USES

Gypsemna's U TRACK is the horizontal top and bottom elements of drywall structure into which the corresponding vertical The Gypsemna's C STUD is fitted. It's strong non load bearing component for exterior and interior drywall partition, ceilings and liners



ADVANTAGES

- For all areas requiring a smoothly finished, monolithic wall plane.
- Fire Resistant Ratings.
- Flexibility of configuration.
- Dimensionally stable.
- Impervious to rot, fungal and insect attack.
- Corrosion resistant.
- Won't warp, twist or bow.
- Easily worked, few tools required.
- Non-combustible.

TECHNICAL DATA

PHYSICAL PROPERTIES

Coating

Z275 Zinc coating / Z180 Zinc coating / Z120 Zinc coating

Standard Compliance

ASTM C645 / ASTM A653 / ASTM A645/ ASTM A370

Material

Cold roll-formed from hot-dipped galvanized steel

Grade

G300

Min Yield Strength

300 mpa

Min Tensile strength

340 mpa

Available Thicknesses (in mm)

0.50, 0.55, 0.6, 0.7
0.8, 0.9, 1.0, 1.1,
1.2, 1.3 and 1.5

Flange (in mm)

32

Width (in mm)

52 , 66 , 72 , 78 , 94 ,
102 , 127 and 152

Length (in mm)

3000