

JADCO AUSTRALASIA





PTW 1103L-9



PTW 1205L-10



PTW 674-05





PTW 7036-2



PTW 8842L-3



PTW 1109-03





PTW 7363-3



PTW 7079-5



PTW 5451-6





PTW 22241-1



PTW 6020



PTW 6035





PTW 6035-2



PTW 6037



PTW 6037-3





PTW 6067-7



PTW 6068-21



PTW 6081-3





PTW 8842L-3



PTW 1156B-2



PTW 1065-7





PTW 1156-1



PTW 1135-16



PTW 0482-2



PTW 1569-9



PTW 0208EL-01



PTW 1135-16



PTW 0110-2



Supplier:	Jadco Australasia	Design	Vinyl Plank Flooring
Material	Resin PVC, Calcium carbonate (Grade A, Stabilizer (environmental))	Usage	Indoor
UV Coating Options	Ceramic Bead/Anti-microbial/Anti-Stain	Thickness	2.0mm to 5.0mm
Backing Options	Imm to 2mm IXPE/EVA/Cork underlayment	Gloss Level	Matt, Glossy
Bevel Treatment	Micro bevel, Painted bevel	Density	1300kgs/M3
Product Name	Plastic Vinyl Flooring for indoor	Feature	Waterproof, Wear Resistant, Anti-slip
Certificate	ISO9001, ISO14001, CE, Floor Score, SGS, VOC, TUV, Greenguard	4 Sides	Dryback, loose lay, Click System
Packing method	Carton, solid wood pallet	Advantage	Eco-friendly / 100% Waterproof

Technical Data

Factory's Test Items	Factory's Standards	Testing Method
Flaw, Crack, Wrinkle, Hold, Separating	Not Allowed	GB4085-83
Color Difference	Two Tones Allowed	GB4085-83
Dirt, Color Change	Not Easily Noticeable	GB4085-83
Specifications		
Length Measurement	± 0.1mm(≤6")	EN427
	± 0.3mm(12" - 24")	
	± 0.5mm(≥36")	
Overall Thickness	± 0.15mm	EN428
Squareness	≤0.25mm	EN427
Straightness	≤0.25mm	EN427
Physical Statistics		
Dimensional Stability to Heat	≤0.12%	EN434
	(80°C, 6Hrs)	
Curling After Exposure To Heat	≤1.2mm	EN434
	(80°C, 6Hrs)	
Wear Resistance	≤0.015g	EN-660-2
Pool Resistance	≥2.8Kgf/2cm	EN431
Residual Indentation After Static Loading	≤0.1mm	EN434
Flexibility	No Damage	EN435
All products comply to EN 14041:2004 Safety Standards		
Product Specifications	Standard	Testing Method
Reaction to Fire	Class Bfl-s1	EN717-1
Formaldehyde Emission	Not Detected	EN717-1
Determination of migration of heavy metals	Not Detected	EN71
Effect of a caster chair	Pass	EN425
Color Fastness to Light	Grade(Blue Wool Std):6	EN ISO 105 B02

